



Certificate of Analysis

Page 1 of 2

Client:	Hawkes Bay Regional Council	Lab No:	2339791	SPv1
Contact:	Ariana Mackay	Date Received:	12-Mar-2020	
	C/- Hawkes Bay Regional Council	Date Reported:	23-Mar-2020	
	Private Bag 6006	Quote No:	99522	
	Napier 4142	Order No:	RM1038	
		Client Reference:	Whangawehi (alternative month)	
		Add. Client Ref:	312-302	
		Submitted By:	Ariana Mackay	

Sample Type: Aqueous

Sample Name:	76676 - Whangawehi at George Ormonds -3301	76677 - Taiporutu Stream at Mo - 4308	76678 - Mangatupae Strm at Pat O'Brians-3303		
	11-Mar-2020 9:15 am	11-Mar-2020 10:30 am	11-Mar-2020 11:30 am		
Lab Number:	2339791.1	2339791.2	2339791.3		
Faecal Coliforms and E. coli profile					
Faecal Coliforms	cfu / 100mL	230	2,400	100 #1	-
Escherichia coli	cfu / 100mL	210	2,200	30 #1	-
HBRC Standard River					
Turbidity ISO	FNU	0.57	2.4	0.35	-
pH	pH Units	7.9	7.9	7.9	-
Electrical Conductivity (EC)	mS/m	57.6	175.4	57.3	-
Volatile Suspended Solids	g/m ³	0.6	5.1	1.0	-
Total Suspended Solids	g/m ³	1.1	28	1.8	-
Total Nitrogen	g/m ³	0.30	0.27	0.27	-
Total Ammoniacal-N	g/m ³	< 0.005	< 0.005	< 0.005	-
Nitrite-N	g/m ³	< 0.0010	< 0.0010	< 0.0010	-
Nitrate-N	g/m ³	0.0010	< 0.0010	0.0016	-
Nitrate-N + Nitrite-N	g/m ³	0.0016	< 0.0010	0.0022	-
Total Kjeldahl Nitrogen (TKN)	g/m ³	0.30	0.27	0.26	-
Dissolved Reactive Phosphorus	g/m ³	0.096	0.0048	0.047	-
Total Phosphorus	g/m ³	0.109	0.018	0.054	-

Analyst's Comments

#1 Statistically estimated count based on the theoretical countable range for the stated method.

Summary of Methods

The following table(s) gives a brief description of the methods used to conduct the analyses for this job. The detection limits given below are those attainable in a relatively simple matrix. Detection limits may be higher for individual samples should insufficient sample be available, or if the matrix requires that dilutions be performed during analysis. A detection limit range indicates the lowest and highest detection limits in the associated suite of analytes. A full listing of compounds and detection limits are available from the laboratory upon request. Unless otherwise indicated, analyses were performed at Hill Laboratories, 28 Duke Street, Frankton, Hamilton 3204.

Sample Type: Aqueous

Test	Method Description	Default Detection Limit	Sample No
Individual Tests			
Filtration, Unpreserved	Sample filtration through 0.45µm membrane filter.	-	1-3
Turbidity - ISO 7027 Method	Analysis using a Hach 2100N IS, Turbidity meter. ISO 7027:1999(E) (modified).	0.05 FNU	1-3



Sample Type: Aqueous			
Test	Method Description	Default Detection Limit	Sample No
pH	pH meter. APHA 4500-H ⁺ B 23 rd ed. 2017. Note: It is not possible to achieve the APHA Maximum Storage Recommendation for this test (15 min) when samples are analysed upon receipt at the laboratory, and not in the field. Samples and Standards are analysed at an equivalent laboratory temperature (typically 18 to 22 °C). Temperature compensation is used.	0.1 pH Units	1-3
Electrical Conductivity (EC)	Conductivity meter, 25°C. APHA 2510 B 23 rd ed. 2017.	0.1 mS/m	1-3
Volatile Suspended Solids	Filtration (GF/C, 1.2 µm). Ashing 550°C, 30 min. Gravimetric. APHA 2540 E (modified) 23 rd ed. 2017.	0.5 g/m ³	1-3
Total Suspended Solids	Filtration of a 2L sample using Whatman 934 AH, Advantec GC-50 or equivalent filters (nominal pore size 1.2 - 1.5µm), gravimetric determination. APHA 2540 D (modified) 23 rd ed. 2017.	0.5 g/m ³	1-3
Total Nitrogen	Calculation: TKN + Nitrate-N + Nitrite-N. Please note: The Default Detection Limit of 0.05 g/m ³ is only attainable when the TKN has been determined using a trace method utilising duplicate analyses. In cases where the Detection Limit for TKN is 0.10 g/m ³ , the Default Detection Limit for Total Nitrogen will be 0.11 g/m ³ .	0.05 g/m ³	1-3
Total Ammoniacal-N Trace	Phenol/hypochlorite colorimetry. Flow injection analyser. (NH ₄ -N = NH ₄ ⁺ -N + NH ₃ -N). APHA 4500-NH ₃ H 23 rd ed. 2017.	0.005 g/m ³	1-3
Nitrite-N Trace	Automated Azo dye colorimetry, Flow injection analyser. APHA 4500-NO ₃ ⁻ I (modified) 23 rd ed. 2017.	0.0010 g/m ³	1-3
Nitrate-N	Calculation: (Nitrate-N + Nitrite-N) - NO ₂ N. In-House.	0.0010 g/m ³	1-3
Nitrate-N + Nitrite-N Trace	Total oxidised nitrogen. Automated cadmium reduction, flow injection analyser. APHA 4500-NO ₃ ⁻ I (modified) 23 rd ed. 2017.	0.0010 g/m ³	1-3
Total Kjeldahl Nitrogen (TKN)	Total Kjeldahl digestion, phenol/hypochlorite colorimetry. Discrete Analyser. APHA 4500-N _{org} D (modified) 4500 NH ₃ F (modified) 23 rd ed. 2017.	0.10 g/m ³	1-3
Dissolved Reactive Phosphorus (trace)	Filtered sample. Molybdenum blue colorimetry. Flow injection analyser. APHA 4500-P G 23 rd ed. 2017.	0.0010 g/m ³	1-3
Total Phosphorus	Total phosphorus digestion, ascorbic acid colorimetry. Discrete Analyser. APHA 4500-P B & E (modified from manual analysis and also modified to include a reductant to reduce interference from any arsenic present in the sample) 23 rd ed. 2017. NWASCO, Water & soil Miscellaneous Publication No. 38, 1982.	0.004 g/m ³	1-3
HBRC Standard River		-	1-3
Faecal Coliforms and E. coli profile			
Faecal Coliforms	Membrane Filtration, Count on mFC agar, Incubated at 44.5°C for 22 hours, Confirmation. APHA 9222 D 23 rd ed. 2017.	1 cfu / 100mL	1-3
Escherichia coli	Membrane filtration, Count on mFC agar, Incubated at 44.5°C for 22 hours, MUG Confirmation. APHA 9222 I 23 rd ed. 2017.	1 cfu / 100mL	1-3

These samples were collected by yourselves (or your agent) and analysed as received at the laboratory.

Dates of testing are available on request. Please contact the laboratory for more information.

Samples are held at the laboratory after reporting for a length of time based on the stability of the samples and analytes being tested (considering any preservation used), and the storage space available. Once the storage period is completed, the samples are discarded unless otherwise agreed with the customer. Extended storage times may incur additional charges.

This certificate of analysis must not be reproduced, except in full, without the written consent of the signatory.



Graham Corban MSc Tech (Hons)
Client Services Manager - Environmental