



Certificate of Analysis

Page 1 of 2

Client:	Hawkes Bay Regional Council	Lab No:	2587228	SPv1
Contact:	Ariana Mackay	Date Received:	17-Apr-2021	
	C/- Hawkes Bay Regional Council	Date Reported:	27-Apr-2021	
	Private Bag 6006	Quote No:	105685	
	Napier 4142	Order No:	RM1368	
		Client Reference:	Whangawehi (April)	
		Add. Client Ref:	312-200	
		Submitted By:	Ariana Mackay	

Sample Type: Aqueous

Sample Name:		80774 - Whangawehi at George Ormonds -3301 16-Apr-2021 11:30 am	80776 - Mangatupae Strm at Pat O'Brians-3303 16-Apr-2021 2:30 pm			
Lab Number:		2587228.1	2587228.2			
Faecal Coliforms and E. coli profile						
Faecal Coliforms	cfu / 100mL	20 #4	20 #4	-	-	-
Escherichia coli	cfu / 100mL	20 #4	20 #4	-	-	-
HBRC Standard River						
Turbidity ISO	FNU	0.36	0.16	-	-	-
pH	pH Units	8.0	7.8	-	-	-
Electrical Conductivity (EC)	µS/cm	584	775	-	-	-
Volatile Suspended Solids	g/m ³	0.8 #2	< 0.5	-	-	-
Total Suspended Solids	g/m ³	0.8 #2	0.5	-	-	-
Total Nitrogen	g/m ³	0.21	0.20	-	-	-
Total Ammoniacal-N	g/m ³	< 0.05 #3	< 0.05 #3	-	-	-
Nitrite-N	g/m ³	< 0.0010	< 0.0010	-	-	-
Nitrate-N	g/m ³	< 0.0010	0.0015	-	-	-
Nitrate-N + Nitrite-N	g/m ³	0.0012	0.0020	-	-	-
Total Kjeldahl Nitrogen (TKN)	g/m ³	0.21	0.20	-	-	-
Dissolved Reactive Phosphorus	g/m ³	0.075 #1	0.027 #1	-	-	-
Total Phosphorus	g/m ³	0.075 #1	0.023 #1	-	-	-

Analyst's Comments

#1 It has been noted that the result for Dissolved Reactive Phosphorus was greater than that for Total Phosphorus, but within the analytical variation of these methods.

#2 It has been noted that the result for Volatile Suspended Solids was greater than that for Total Suspended Solids, but within the analytical variation of these methods.

#3 Severe matrix interferences required that a dilution be performed prior to analysis, resulting in a detection limit higher than that normally achieved for the NH4N analysis.

#4 Statistically estimated count based on the theoretical countable range for the stated method.

Please interpret this result with caution as the sample was > 10 °C on receipt at the lab. The sample temperature is recommended by the laboratory's reference methods to be less than 10 °C on receipt at the laboratory (but not frozen). However, it is acknowledged that samples that are transported quickly to the laboratory after sampling, may not have been cooled to this temperature.



This Laboratory is accredited by International Accreditation New Zealand (IANZ), which represents New Zealand in the International Laboratory Accreditation Cooperation (ILAC). Through the ILAC Mutual Recognition Arrangement (ILAC-MRA) this accreditation is internationally recognised. The tests reported herein have been performed in accordance with the terms of accreditation, with the exception of tests marked * or any comments and interpretations, which are not accredited.

Summary of Methods

The following table(s) gives a brief description of the methods used to conduct the analyses for this job. The detection limits given below are those attainable in a relatively simple matrix. Detection limits may be higher for individual samples should insufficient sample be available, or if the matrix requires that dilutions be performed during analysis. A detection limit range indicates the lowest and highest detection limits in the associated suite of analytes. A full listing of compounds and detection limits are available from the laboratory upon request. Unless otherwise indicated, analyses were performed at Hill Laboratories, 28 Duke Street, Frankton, Hamilton 3204.

Sample Type: Aqueous			
Test	Method Description	Default Detection Limit	Sample No
Individual Tests			
Filtration, Unpreserved	Sample filtration through 0.45µm membrane filter.	-	1-2
Turbidity - ISO 7027 Method	Analysis using a Hach 2100N IS, Turbidity meter. ISO 7027:1999(E) (modified).	0.05 FNU	1-2
pH	pH meter. APHA 4500-H ⁺ B 23 rd ed. 2017. Note: It is not possible to achieve the APHA Maximum Storage Recommendation for this test (15 min) when samples are analysed upon receipt at the laboratory, and not in the field. Samples and Standards are analysed at an equivalent laboratory temperature (typically 18 to 22 °C). Temperature compensation is used.	0.1 pH Units	1-2
Electrical Conductivity (EC)	Conductivity meter, 25°C. APHA 2510 B 23 rd ed. 2017.	1 µS/cm	1-2
Volatile Suspended Solids	Filtration (GF/C, 1.2 µm). Ashing 550°C, 30 min. Gravimetric. APHA 2540 E (modified) 23 rd ed. 2017.	0.5 g/m ³	1-2
Total Suspended Solids	Filtration of a 2L sample using Whatman 934 AH, Advantec GC-50 or equivalent filters (nominal pore size 1.2 - 1.5µm), gravimetric determination. APHA 2540 D (modified) 23 rd ed. 2017.	0.5 g/m ³	1-2
Total Nitrogen	Calculation: TKN + Nitrate-N + Nitrite-N. Please note: The Default Detection Limit of 0.05 g/m ³ is only attainable when the TKN has been determined using a trace method utilising duplicate analyses. In cases where the Detection Limit for TKN is 0.10 g/m ³ , the Default Detection Limit for Total Nitrogen will be 0.11 g/m ³ . In-house calculation.	0.05 g/m ³	1-2
Total Ammoniacal-N Trace	Phenol/hypochlorite colorimetry. Flow injection analyser. (NH ₄ -N = NH ₄ ⁺ -N + NH ₃ -N). APHA 4500-NH ₃ H 23 rd ed. 2017.	0.005 g/m ³	1-2
Nitrite-N Trace	Automated Azo dye colorimetry, Flow injection analyser. APHA 4500-NO ₂ ⁻ I (modified) 23 rd ed. 2017.	0.0010 g/m ³	1-2
Nitrate-N	Calculation: (Nitrate-N + Nitrite-N) - NO ₂ N. In-House.	0.0010 g/m ³	1-2
Nitrate-N + Nitrite-N Trace	Total oxidised nitrogen. Automated cadmium reduction, flow injection analyser. APHA 4500-NO ₃ ⁻ I (modified) 23 rd ed. 2017.	0.0010 g/m ³	1-2
Total Kjeldahl Nitrogen (TKN)	Total Kjeldahl digestion, phenol/hypochlorite colorimetry. Discrete Analyser. APHA 4500-N _{org} D (modified) 4500 NH ₃ F (modified) 23 rd ed. 2017.	0.10 g/m ³	1-2
Dissolved Reactive Phosphorus (trace)	Filtered sample. Molybdenum blue colorimetry. Flow injection analyser. APHA 4500-P G 23 rd ed. 2017.	0.0010 g/m ³	1-2
Total Phosphorus	Total phosphorus digestion, automated ascorbic acid colorimetry. Flow Injection Analyser. APHA 4500-P H 23 rd ed. 2017.	0.002 g/m ³	1-2
HBRC Standard River		-	1-2
Faecal Coliforms and E. coli profile			
Faecal Coliforms	Membrane Filtration, Count on mFC agar, Incubated at 44.5°C for 22 hours, Confirmation. APHA 9222 D 23 rd ed. 2017.	1 cfu / 100mL	1-2
Escherichia coli	Membrane filtration, Count on mFC agar, Incubated at 44.5°C for 22 hours, MUG Confirmation. APHA 9222 I 23 rd ed. 2017.	1 cfu / 100mL	1-2

These samples were collected by yourselves (or your agent) and analysed as received at the laboratory.

Testing was completed between 18-Apr-2021 and 27-Apr-2021. For completion dates of individual analyses please contact the laboratory.

Samples are held at the laboratory after reporting for a length of time based on the stability of the samples and analytes being tested (considering any preservation used), and the storage space available. Once the storage period is completed, the samples are discarded unless otherwise agreed with the customer. Extended storage times may incur additional charges.

This certificate of analysis must not be reproduced, except in full, without the written consent of the signatory.

Ara Heron BSc (Tech)
Client Services Manager - Environmental